

MP 71

Single Point Load Cell



5kg ... 200kg

- Aluminium alloy construction
- Compatible with other sources
- Single point 400mm x 400mm platform
- Approved according to OIML R60

Applications

- Bench Scales
- Counting Scales
- Check Weighing Systems

Technical Data		C3MR	
Accuracy class (Combined error)		0.020	% C _n
Maximum capacity	E _{max}	5 / 10 / 20 / 30 / 50 / 100 / 200	kg
Maximum usable load	E _u	150	% E _{max}
Destructive load	E _d	≥ 300	% E _{max}
Safe side load	E _{Iq}	100	% E _{max}
Maximum number of LC intervals	n _{LC}	3,000	
Minimum LC verification interval v _{min} = E _{max} /Y	Y	15,000	
Rated output	C _n	2.0	mV/V
Tolerance on rated output	D _c	≤ ± 10	% C _n
Zero output signal	S _{min}	≤ ± 5	% C _n
Creep, during 30 min.	d _{cr}	≤ ± 0.016	% C _n
Temperature effect on S _{min}	TK _{Smin}	≤ ± 0.009	% C _n / 10K
Temperature effect on C	TK _C	≤ ± 0.010	% C _n / 10K
Input impedance	R _{LC}	413 ± 20	Ω
Output impedance	R _o	350 ± 25	Ω
Insulation impedance (100V DC)	R _{I5}	≥ 5	GΩ
Recommended supply voltage	B _u	5 ... 15	V
Nominal ambient temperature range	B _T	- 10 ... + 40	°C
Usable ambient temperature range	B _{Tu}	- 20 ... + 65	°C
Nominal deflection	S _{nom}	0.56 (E _{max} =5kg); 0.46 (E _{max} =10kg); 0.39 (E _{max} =20kg); 0.38 (E _{max} =30kg); 0.37 (E _{max} =50kg); 0.39 (E _{max} =100kg); 0.48 (E _{max} =200kg)	mm
Cable length		1.5 (other lengths optional)	m
Cable type		6 conductor TPE cable (AWG 26), shield grounded (optional: shield floating)	
Sensor material		Aluminium	
Protection class (acc. to IEC 529)		IP67	

The technical data given here serve only as a product description and must not be interpreted as guaranteed characteristics in legal sense.

По вопросам продаж и поддержки обращайтесь:

Астана+7(7172)727-132, Волгоград(844)278-03-48, Воронеж(473)204-51-73, Екатеринбург(343)384-55-89,
Казань(843)206-01-48, Краснодар(861)203-40-90, Красноярск(391)204-63-61, Москва(495)268-04-70,
Нижний Новгород(831)429-08-12, Новосибирск(383)227-86-73, Ростов-на-Дону(863)308-18-15, Самара(846)206-03-16,
Санкт-Петербург(812)309-46-40, Саратов(845)249-38-78, Уфа(347)229-48-12

sst@nt-rt.ru || sartorius.nt-rt.ru

